

27 August 2024

Oracle Power PLC
("Oracle" or the "Company")

Gold Target Zone Increased with Latest Drilling at Northern Zone Project

Oracle Power PLC (AIM:ORCP), an international project developer, is pleased to announce that it has received further assay results from the recently completed 1,903m Aircore (AC) drilling campaign at the Northern Zone Intrusive Hosted Gold Project ("Northern Zone" or the "Project").

Highlights:

- Highest grade interval to date from shallow drilling of 27.5 g/t gold (drill hole NZAC033) recorded over 1 metre in recently completed drilling.
- Significant shallow gold intercepts, include:
 - 16m @ 4.69 g/t Au from 30m (drill hole NZAC033)
 - 4m @ 6.9 g/t Au from 39m (drill hole NZAC029)
 - 3m @ 3.32 g/t Au from 35m (drill hole NZAC030)
 - 9m @ 1.2 g/t Au from 31m (drill hole NZAC048)
 - 3m @ 2.68 g/t Au from 31m (drill hole NZAC043)
 - 3m @ 2.11 g/t Au from 46m (drill hole NZAC044)
 - 4m @ 1.47 g/t Au from 30m (drill hole NZAC053)
- Single metre assay of drill hole NZRC001 has now been completed returning a higher-grade core that includes:
 - 10m @ 4.94g/t Au from 39m (NZRC001)^[1]
 - Or 14m @ 3.6/t Au from 39m
 - Or 18m @ 2.8g/t Au from 36m (if the same interval as the composite).
- Further step-out targeted drilling is now being planned over the expanded footprint of the mineralised porphyry.

Naheed Memon, CEO of Oracle, commented:

"These latest gold results are very exciting for the Project and it is great to be able to back up initial results at Northern Zone, with this latest run of assays so quickly after the recent success of our maiden RC and AC campaigns. The results indicate that we have very significant shallow supergene and oxide gold mineralisation and that targeting this mineralisation has generated positive results that far exceed our expectations. We suspect that we have a number of these high-grade zones overlying this extensive gold mineralised porphyry system and the next drill programme will test this expansive shallow model."

"New drilling, which is being planned, will focus on heading to the north-east, north-west and south-east, where the maiden diamond drilling traverse intersected mineralisation down to 450 metres and in excess of 150 metres thick in the un-weathered underlying porphyry^[2]. The identification of a fault, believed to be a controlling feature of mineralisation in the area will also be targeted in a follow up drill programme, that will be finalised shortly. We look forward to the results from the next round of drilling which we are hopeful in starting within weeks."

As previously announced, the Northern Zone Project has an Exploration Target of 200 to 250 million tonnes at a grade of 0.4 g/t to 0.6 g/t Au for 2.5 to 4.8 million oz of gold, as announced by Riversgold Limited (ASX:RGL) to the ASX on 9 May 2023.

Cautionary Statement: The potential quantity and grade of the Exploration Target is conceptual in nature. There has been insufficient exploration to estimate a Mineral Resource and it is uncertain if further exploration will result in the

estimation of a Mineral Resource. The reader is advised that an Exploration Target is based on existing drill results and geological observations from drilling as well as interpretation of multiple available datasets. The Exploration Target is based on historical and more recent Oracle drilling results. It uses data from 53 historical drillholes drilled between 1998 and 2012, and seven drillholes drilled by Oracle in 2021.

Further Information

Drilling contractor Australian Aircore Drilling (Mick Shorter) completed a further 26 holes for 1,903m of AC drilling at Northern Zone using a blade to drilling refusal, with the cuttings being logged by Riversgold Limited's ("RGL") geologists. The detailed logging and assays continue to show that a significant gold mineralisation event has occurred in the Project area. The drilling targeted the shallower, up dip portion of the mineralised system, that yielded a significant composite intercept of **18m @ 4.14g/t Au from 36m** (drill hole NZRC001)^[3].

Single metre assay of drill hole NZRC001 has now been completed returning a higher-grade core of **10m @ 4.94g/t Au from 38m** or **14m @ 3.6/t Au from 38m** or **18m @ 2.8g/t Au from 36m** if the same interval as the composites is used.

Recent Aircore drilling has replicated zones of gold mineralisation seen in drill hole NZRC001 with **16m @ 4.69 g/t Au from 30m** (drill hole NZAC033), **4m @ 6.9 g/t Au from 39m** (drill hole NZAC029), **3m @ 3.32 g/t Au from 35m** (drill hole NZAC030) and **9m @ 1.2 g/t Au from 31m** (drill hole NZAC048).

Mineralisation remains open in multiple directions, necessitating further drilling campaigns. Refer to Figure 1 for drilling locations, and Tables 1-4 for location and assay results.

ENDS

For further information, visit www.oraclepower.co.uk or contact:

Oracle Power PLC
Naheed Memon - CEO

+44 (0) 20 7236 1177

Strand Hanson Limited (Nominated Adviser & Broker)
Rory Murphy, Matthew Chandler, Rob Patrick

+44 (0) 20 7409 3494

St Brides Partners Limited (Financial PR)
Isabel de Salis, Susie Geliher

oracle@stbridespartners.co.uk

This announcement contains inside information for the purposes of Article 7 of EU Regulation No. 596/2014, which forms part of United Kingdom domestic law by virtue of the European (Withdrawal) Act 2018, as amended.

Competent Person's Statement

The information in this announcement that relates to exploration results, mineral resources or ore reserves is based on information compiled by Mr Edward Mead, who is a Fellow of the Australasian Institute of Mining and Metallurgy. Mr Mead is a consultant to the Company. Mr Mead has sufficient experience which is relevant to the style of mineralisation and type of deposits under consideration and to the activity that he is undertaking to qualify as a Competent Person as defined in the 2012 edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves' (the JORC Code). Mr Mead consents to the inclusion of this information in the form and context in which it appears in this announcement.






Figure 1: Drill collar plan with gold grade contours from all drilling results to date, section line (Figure 2), and proposed next phase of drilling.




Figure 2: Oblique Schematic cross section. 1.5 times vertical exaggeration. Geology, supergene mineralisation and oxide mineralisation interpretation with significant intercepts. Refer to Location Map inset for section line. Refer to Figure 1 for all drill hole locations and section lines.

APPENDIX 1: Drilling Information

Table 1: Northern Zone Significant Intercepts

Hole ID	From (m)	To (m)	Width (m)	Au g/t	Intercept
NZAC029	39	43	4	6.9	4m @ 6.9 g/t Au from 39m
NZAC029	54	56	2	1.89	2m @ 1.89 g/t Au from 54m
NZAC030	35	38	3	3.32	3m @ 3.32 g/t Au from 35m
NZAC030	51	54	3	0.6	3m @ 0.6 g/t Au from 51m
NZAC030	59	61	2	3.89	2m @ 3.89 g/t Au from 59m
NZAC031	34	35	1	1.8	1m @ 1.8 g/t Au from 34m
NZAC032	33	35	2	1.4	2m @ 1.4 g/t Au from 33m
NZAC032	55	56	1	1.16	1m @ 1.16 g/t Au from 55m
NZAC032	76	77	1	3.78	1m @ 3.78 g/t Au from 76m
NZAC032	88	91	3	1.17	3m @ 1.17g/t Au from 88m
NZAC033	30	46	16	4.69	16m @ 4.69 g/t Au from 30m
NZAC034	32	33	1	1.2	1m @ 1.2 g/t Au from 32m
NZAC035	36	37	1	4.87	1m @ 4.87 g/t Au from 36m
NZAC037	45	47	2	4	2m @ 4.0 g/t Au from 45m
NZAC038	50	51	1	4.2	1m @ 4.2 g/t Au from 50m
NZAC039	31	35	4	0.64	3m @ 0.78 g/t Au from 32m
NZAC039	68	70	2	0.87	2m @ 0.87 g/t Au from 68m
NZAC040	49	50	1	2.39	1m @ 2.39 g/t Au from 49m
NZAC041	77	78	1	10	1m @ 10.0 g/t Au from 77m
NZAC042	38	39	1	0.61	1m @ 0.61 g/t Au from 38m
NZAC043	31	34	3	2.68	3m @ 2.68 g/t Au from 31m
NZAC043	56	57	1	0.79	1m @ 0.79 g/t Au from 56m
NZAC044	47	52	5	1.34	3m @ 2.11 g/t Au from 46m
NZAC047	51	52	1	1.72	1m @ 1.72 g/t Au from 51m
NZAC048	31	40	9	1.2	9m @ 1.2 g/t Au from 31m
NZAC051	36	37	1	1.66	1m @ 1.66 g/t Au from 36m
NZAC053	30	34	4	1.47	4m @ 1.47 g/t Au from 30m
NZRC001	38	48	10	4.94	10m @ 4.94g/t Au from 38m
NZRC001	38	52	14	3.6	or 14m @ 3.6/t Au from 38m
NZRC001	36	54	18	2.8	or 18m @ 2.8g/t Au from 36m

Table 2: Northern Zone Aircore Drill Collar Locations and information, in GDA Zone 51J.

Hole_ID	East	North	Elevation	Depth (m)	Dip	Azimuth
NZAC028	381472	6592575	356	71	-90	0
NZAC029	381499	6592576	356	81	-90	0
NZAC030	381525	6592575	356	76	-90	0
NZAC031	381549	6592577	356	60	-90	0
NZAC032	381474	6592603	356	91	-90	0
NZAC033	381501	6592599	356	77	-90	0
NZAC034	381525	6592599	356	60	-90	0
NZAC035	381547	6592599	356	55	-90	0
NZAC036	381475	6592550	356	90	-90	0
NZAC037	381501	6592547	356	90	-90	0
NZAC038	381527	6592552	356	84	-90	0

Hole ID	East	North	Elevation	Depth (m)	Dip	Azimuth
NZAC040	381474	6592530	356	84	-90	0
NZAC041	381501	6592528	356	90	-90	0
NZAC042	381523	6592527	356	88	-90	0
NZAC043	381551	6592524	356	78	-90	0
NZAC044	381499	6592505	356	90	-90	0
NZAC045	381547	6592502	356	57	-90	0
NZAC046	381547	6592497	356	82	-90	0
NZAC047	381478	6592627	356	74	-90	0
NZAC048	381499	6592626	356	69	-90	0
NZAC049	381525	6592626	356	56	-90	0
NZAC050	381549	6592646	356	47	-90	0
NZAC051	381504	6592646	356	58	-90	0
NZAC052	381601	6592507	356	66	-90	0
NZAC053	381604	6592549	356	58	-90	0

Table 3: Northern Zone Individual metre assays from NZRC001, 002 and 006

Hole ID	From (m)	To (m)	Width (m)	Au Grade (g/t)
NZRC001	36	37	1	0.09
NZRC001	37	38	1	0.07
NZRC001	38	39	1	1.26
NZRC001	39	40	1	22.70
NZRC001	40	41	1	1.11
NZRC001	41	42	1	0.10
NZRC001	42	43	1	1.16
NZRC001	43	44	1	0.73
NZRC001	44	45	1	15.65
NZRC001	45	46	1	0.81
NZRC001	46	47	1	1.07
NZRC001	47	48	1	4.77
NZRC001	48	49	1	0.07
NZRC001	49	50	1	0.23
NZRC001	50	51	1	0.02
NZRC001	51	52	1	0.56
NZRC001	52	53	1	0.07
NZRC001	53	54	1	0.01
NZRC002	36	37	1	0.83
NZRC002	37	38	1	0.56
NZRC002	38	39	1	0.10
NZRC002	39	43	1	2.01
NZRC002	43	44	1	0.68
NZRC002	44	45	1	0.21
NZRC006	57	58	1	0.02
NZRC006	58	59	1	0.01
NZRC006	59	60	1	2.67

Table 4: Northern Zone AC Results > 0.5 Au Grade (g/t) Cutoff

Hole ID	From (m)	To (m)	Width (m)	Au Grade (g/t)
NZAC029	39	40	1	26.30
NZAC029	40	41	1	0.64
NZAC029	54	55	1	0.70
NZAC029	55	56	1	3.08
NZAC030	35	36	1	0.86
NZAC030	36	37	1	8.15
NZAC030	37	38	1	0.94
NZAC030	40	41	1	0.53
NZAC030	51	52	1	0.82
NZAC030	53	54	1	0.54
NZAC030	59	60	1	1.47
NZAC030	60	61	1	6.30
NZAC031	34	35	1	1.80
NZAC031	59	60	1	0.88
NZAC032	34	35	1	1.05
NZAC032	35	36	1	1.68
NZAC032	55	56	1	1.16
NZAC032	76	77	1	3.78
NZAC032	88	89	1	1.42
NZAC032	89	90	1	0.86
NZAC032	90	91	1	1.24
NZAC033	30	31	1	0.90
NZAC033	31	32	1	1.08
NZAC033	36	37	1	1.73
NZAC033	37	38	1	11.95
NZAC033	38	39	1	25.50
NZAC033	39	40	1	27.50
NZAC033	40	41	1	2.85
NZAC033	41	42	1	0.75
NZAC033	42	43	1	0.75
NZAC034	32	33	1	1.20
NZAC034	34	35	1	0.80
NZAC035	36	37	1	4.87
NZAC035	38	39	1	0.91
NZAC037	45	46	1	3.71
NZAC037	46	47	1	4.26
NZAC038	50	51	1	4.20
NZAC038	62	63	1	0.55
NZAC039	32	33	1	1.56
NZAC039	47	48	1	0.51
NZAC039	68	69	1	1.37
NZAC040	49	50	1	2.29
NZAC041	77	78	1	10.00
NZAC042	38	39	1	0.61
NZAC043	32	33	1	7.31
NZAC043	56	57	1	0.79

NZAC004	From (m)	To (m)	Width (m)	Au Grade (g/t)
NZAC044	50	51	1	4.15
NZAC046	80	81	1	0.67
NZAC047	51	52	1	1.72
NZAC048	32	33	1	0.77
NZAC048	33	34	1	3.54
NZAC048	34	35	1	1.24
NZAC048	36	37	1	0.71
NZAC048	37	38	1	2.19
NZAC048	38	39	1	0.54
NZAC048	40	41	1	1.42
NZAC050	43	44	1	0.68
NZAC051	32	33	1	1.08
NZAC051	36	37	1	1.66
NZAC051	52	53	1	0.73
NZAC053	30	31	1	1.37
NZAC053	32	33	1	0.83
NZAC053	33	34	1	3.41

APPENDIX 2: JORC INFORMATION

The following Tables are provided to ensure compliance with the JORC Code (2012 Edition) requirements for the reporting of Exploration Results at Northern Zone.

Section 1: Sampling Techniques and Data

(Criteria in this section applies to all succeeding sections)

Criteria	JORC Code explanation	Commentary
Sampling techniques	<p><i>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i></p> <p><i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i></p> <p><i>Aspects of the determination of mineralisation that are Material to the Public Report.</i></p> <p><i>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay). In other cases, more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</i></p>	<p>Every metre drilled was placed on the ground.</p> <p>6m composites were collected using a scoop method of sampling the coarse reject sample for the first 24m</p> <p>1m sampling using a rifle splitter was trialled on the clays, from 24m, with sampling deemed to create a high degree risk of smearing. The clays are not wet, but have a damp characteristic. A large metal scoop was used to sample between 70-90% of material from each metre drilled, to total between 2-3kg samples.</p> <p>Standard reference material, sample duplicates and blanks, were undertaken at 25m sample intervals.</p> <p>Samples were sent to the laboratory for crushing, splitting and analysis.</p> <p>Analysis was undertaken by ALS laboratories (Kalgoorlie) for gold assay by 50g fire assay.</p>
Drilling techniques	<p><i>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i></p>	<p>Australian Aircore Drilling completed the program using a blade to refusal. A hammer was used on 10m in hole NZAC053 due to a hard silica layer.</p>
Drill sample recovery	<p><i>Method of recording and assessing core and chip sample recoveries and results assessed.</i></p> <p><i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i></p> <p><i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i></p>	<p>Drill recovery was routinely recorded via estimation of the comparative percentage of the volume of the sample pile by the company geologist.</p> <p>The sample recovery was deemed excellent for representative assays, with consistent sample recovery and no loss though the top of the cyclone.</p> <p>The cyclone was cleaned or checked every 3m.</p>

Criteria	JORC Code explanation	Commentary
Logging	<p>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</p> <p>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</p> <p>The total length and percentage of the relevant intersections logged.</p>	<p>All holes have been geologically logged for lithology, mineralisation and weathering. As well as whether dry, damp or wet.</p> <p>A brief description of each drilling sample was recorded and a permanent record has been collected and stored in chip trays for reference.</p>
Sub-sampling techniques and sample preparation	<p>If core, whether cut or sawn and whether quarter, half or all core taken.</p> <p>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</p> <p>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</p> <p>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</p> <p>Measures taken to ensure that the sampling is representative of the in-situ material collected, including for instance results for field duplicate/second-half sampling.</p> <p>Whether sample sizes are appropriate to the grain size of the material being sampled.</p>	<p>1m sampling using a rifle splitter was trialed on the clays, from 24m with sampling deemed to create a high degree risk of smearing. The clays are not wet, but have a damp characteristic. A large metal scoop was used to sample between 70-90% of material from each metre drilled, to total between 2-3kg samples.</p> <p>Standard reference material, sample duplicates and blanks, were undertaken at 25m sample intervals.</p> <p>Samples were sent to the laboratory for crushing, splitting and analysis.</p> <p>The use of fire assay with 50g charge for all AC drilling provides a level of confidence in the assay database. The sampling and assaying are considered representative of the in-situ material.</p> <p>The sample size of 2-3 kilograms is appropriate and representative of the grain size and mineralisation style of the deposit.</p>
Quality of assay data and laboratory tests	<p>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</p> <p>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</p> <p>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</p>	<p>ALS (Kalgoorlie) were used for all analysis of drill samples submitted by Riversgold. The laboratory techniques below are for all samples submitted to ALS and are considered appropriate for the style of mineralisation defined within the Reedy South Project area:</p> <p>Samples above 3Kg were riffle split.</p> <p>Pulverise to 95% passing 75 microns</p> <p>50-gram Fire Assay (Au-AA26) with ICP finish - Au</p> <p>Duplicates, Standards and Blanks were used for external laboratory checks by RGL.</p>
Verification of sampling and assaying	<p>The verification of significant intersections by either independent or alternative company personnel.</p> <p>The use of twinned holes.</p> <p>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</p> <p>Discuss any adjustment to assay data.</p>	<p>Intercepts were reviewed by 2 company personnel.</p>
Location of data points	<p>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</p> <p>Specification of the grid system used.</p> <p>Quality and adequacy of topographic control.</p>	<p>The collar position of each hole was recorded using handheld Garmin 64S GPS in GDA Zone 51J. All holes will be picked up by a surveyor in the near future.</p>
Data spacing and distribution	<p>Data spacing for reporting of Exploration Results.</p> <p>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</p> <p>Whether sample compositing has been applied.</p>	<p>The holes were drilled on a nominal East-West 25m spacing on traverses 25m apart, North-South.</p> <p>On the schematic cross sections contained in the release the drill holes are 38m apart.</p>
Orientation of data in relation to geological structure	<p>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</p> <p>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</p>	<p>The vertical drill holes were designed to test for supergene mineralisation or weathered primary ore zones and are believed to be unbiased based when interpretation is applied at modelling results.</p>
Sample security	<p>The measures taken to ensure sample security.</p>	<p>Company personnel delivered samples to ALS Kalgoorlie where they were submitted for assay.</p>
Audits or reviews	<p>The results of any audits or reviews of sampling techniques and data.</p>	<p>Data reviews will be conducted on completion of further drilling</p>

Section 2: Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	<p>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</p> <p>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</p>	<p>The Northern Zone Project is comprised of one granted prospecting licence (P25/2651) which covers an area of 82 hectares, and is held in the name of Oracle Gold (WA) Pty Ltd.</p> <p>ASX listed ASX:RGL is farming into the Tenement and have committed to spend \$600,000 in exploration expenditure on the tenement within the next two years. After Riversgold achieves 80% ownership, Oracle will be required to contribute pro-rata or dilute.</p>
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	The majority of previous exploration in the area was by Northern Mining during 2007 to 2012 under the Blair North project, multiple small resource areas were identified at the George's Reward area to the south of P25/2651. Numerous gold intersections were recorded
Geology	Deposit type, geological setting and style of mineralisation.	<p>The deposit is thought to be an Intrusion Related Gold System (IRGS) style of mineral deposit.</p> <p>Further drilling will better define the mineralisation style, and timing of the gold mineralisation event.</p>
Drill hole Information	<p>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</p> <p style="padding-left: 40px;">eastings and northing of the drill hole collar</p> <p style="padding-left: 40px;">elevation or RL (Reduced Level - elevation above sea level in metres) of the drill hole collar</p> <p style="padding-left: 40px;">dip and azimuth of the hole</p> <p style="padding-left: 40px;">down hole length and interception depth</p> <p style="padding-left: 40px;">hole length.</p> <p>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</p>	Refer to Tables and Figures within the body of the release.
Data aggregation methods	<p>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</p> <p>Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</p> <p>The assumptions used for any reporting of metal equivalent values should be clearly stated.</p>	Intersections are weighted average grades based on a 0.001 g/t Au cut-off with unlimited waste zones but with a targeted grade of above 1.0 g/t Au.
Relationship between mineralisation widths and intercept lengths	<p>These relationships are particularly important in the reporting of Exploration Results.</p> <p>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</p> <p>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</p>	<p>The diamond drilling program in 2023 confirmed the apparent widths of mineralisation as being perpendicular to foliation and veining. We believe the step out RC drilling to be the same as the diamond drilling. The true width of mineralisation is still to be fully ascertained.</p> <p>The Aircore drilling was vertical and not designed for true width.</p>
Diagrams	Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.	See body of the announcement for relevant diagrams and photos.
Balanced reporting	Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practised to avoid misleading reporting of Exploration	The reporting of exploration results is considered balanced by the competent person.

Criteria	JORC Code explanation	Commentary
Other substantive exploration data	<i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples - size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i>	See body of the announcement.
Further work	<i>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i>	<ul style="list-style-type: none"> Follow up phases of drilling to further test strike to be undertaken. Core from phase 1 to allow for further metallurgical studies.

-
- [1] Riversgold Limited (ASX:RGL) ASX announcement of 11 July 2024 "Northern Zone Delivers Further High-Grade Gold Intercepts"
- [2] Riversgold Limited (ASX:RGL) ASX announcement of 12 December 2023 "100m Wide Gold Intercepts at Northern Zone Project"
- [3] Riversgold Limited (ASX:RGL) ASX announcement of 11 July 2024 "Northern Zone Delivers Further High-Grade Gold Intercepts"

This information is provided by RNS, the news service of the London Stock Exchange. RNS is approved by the Financial Conduct Authority to act as a Primary Information Provider in the United Kingdom. Terms and conditions relating to the use and distribution of this information may apply. For further information, please contact ms@seg.com or visit www.ms.com.

RNS may use your IP address to confirm compliance with the terms and conditions, to analyse how you engage with the information contained in this communication, and to share such analysis on an anonymised basis with others as part of our commercial services. For further information about how RNS and the London Stock Exchange use the personal data you provide us, please see our [Privacy Policy](#).

END

DRLSEWSWWELSESA